



Product information

Water-based and silicone-free polishing compound designed to quickly and permanently remove sanding scratches on industrial paints from P2000 and finer, leaving a hologram and haze-free deep gloss finish. Specifically developed for dark surfaces and composites.

Product advantages

- Fine polishing compound for production or restoration processes of dark surfaces
- Gives a quick and lasting result
- Easy to wipe and clean
- Water-based and silicone free



Surfaces

- Dark colored gel coat
- Dark colored high gloss lacquers
- Carbon fibre

Polishing machine

- Rotating 800 – 2000 rpm
- Random orbital polisher 6000-10000 rpm

Polishing pad

- Black lambswool pro
- Black foam pad M

Product properties

Speed: 

Polish, gloss: 

Work instruction

1. Shake or stir polishing compound before use
2. Do not use too much compound at a time. Use a small amount which is consumed on a focused area - less messing and clean up!
3. Clean thoroughly before and after polishing
4. Work focused on an area of 40x40 cm at a time
5. Polish until a scratch free surface is achieved
6. Keep the pad clean, a dirty pad causes deep swirls and scratches

Technical specifications

Density: 1,04 kg/l
 Viscosity: 45 000 cP
 Colour: Black
 pH: 7 - 8

Storage recommendations

Recommended storage temperature:
 5° - 35° C / 41° - 95° F
 Keep from freezing
 Shelf life is 3 years from the marked production date.